

HIGH-VOLTAGE INTERFACE DRIVERS

SELECTION GUIDE TO HIGH-VOLTAGE INTERFACE DRIVERS

Device Type	Absolute Maximum Ratings		Outputs
	I_{OUT}	V_{OUT}	
UHP-500 through 533	500 mA	100 V	Sink 4
UCN-4823A	500 mA	100 V	Sink 8
UDN-6116A/R	-40 mA	85 V	Source 6
UDN-6116A-1	-40 mA	115 V	Source 6
UDN-6116A/R-2	-40 mA	65 V	Source 6
UDN-6118A/R	-40 mA	85 V	Source 8
UDN-6118A-1	-40 mA	115 V	Source 8
UDN-6118A/R-2	-40 mA	65 V	Source 8
UDN-6126A/R	-40 mA	85 V	Source 6
UDN-6126A-1	-40 mA	115 V	Source 6
UDN-6126A/R-2	-40 mA	65 V	Source 6
UDN-6128A/R	-40 mA	85 V	Source 8
UDN-6128A-1	-40 mA	115 V	Source 8
UDN-6128A/R-2	-40 mA	65 V	Source 8
UDN-6138A	-40 mA	± 40 V	Source 8
UDN-6138A-2	-40 mA	± 30 V	Source 8
UDN-6148A	-40 mA	± 40 V	Source 8
UDN-6148A-2	-40 mA	± 30 V	Source 8
UDN-6510A/R	-40 mA	200V	Source 8
UDN-6514A/R	-40 mA	140 V	Source 8
UDN-7180A	20 mA	-115 V	Sink 8
UDN-7180A	20 mA	-115 V	Sink 8
UDN-7183A	3.25 mA	-115 V	Sink 8
UDN-7184A	2.0 mA	-115 V	Sink 8
UDN-7186A	1.0 mA	-115 V	Sink 8